


Datasheet

FL1200-GL1200

Manufacture: NEKO LIGHTING AG

Type: FUSION Linear System FL1200(R)F-GL1200-32W-840-BN



General

- Indoor
- Linear System
- Trimless Recessed
- Version: square
- Housing: black
- Reflector: none
- IP 20

LED

- 4000K
- CRI 80
- LED Output: 4800lm
- System Output: 3800lm
- 50000h@L80B10
- SDCM: 3



Description

Trimless Recessed FUSION Linear profile with General Light (GL1200) insert and ON-OFF driver; black profile channel (RAL 9005); LED 32W; measurement 1200mm x 50mm; CCT 4000K with an LED Output of 4800lm; decent colour rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient SAMSUNG LED Chips; 5 years warranty; wide beam characteristic with 105° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work; degree of housing protection according to DIN EN 60529 (IP20)

Light distribution



Technical drawing



Optics

- Beam angle: 105°

Electric

- LED Driver: ON-OFF
- LED Power: 32W
- System Power: 36W
- 46V
- 700mA

Dimensions

- Measurement: 1200mm x 50mm
- Cutout: 1210mm x 52mm
- Height: 95mm
- Ceiling height: 150mm



CB

CE

RoHS



Driver

1210x52mm



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.