

# Datasheet

## FL1500-2\*AL300

Manufacture: NEKO LIGHTING AG

Type: FUSION Linear System FL1500(P)F-2\*AL300-26W-927-15D-B



### General

- Indoor
- Linear System
- Pendant Installation
- Version: square
- Housing: black
- Reflector: black
- IP 20

### LED

- 2700K
- CRI 90
- LED Output: 2400lm
- System Output: 1700lm
- 50000h@L80B10
- SDCM: 3

**OSRAM**

### Optics

- Beam angle: 15°
- UGR <19

### Electric

- LED Driver: ON-OFF
- LED Power: 26W
- System Power: 30W
- 36V
- 700mA


### Dimensions

- Measurement: 1500mm x 50mm
- Height: 95mm

### Description

FUSION Linear profile with two Accent Light inserts and ON-OFF driver as pendant installation; black profile channel (RAL 9005) and black reflector; LED 26W; measurement 1500mm x 50mm; CCT 2700K with an LED Output of 2400lm; high colour rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; narrow beam characteristic with 15° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP20)

### Light distribution



### Technical drawing



CB

CE

RoHS



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.