Datasheet

FL1800-WW1800

Manufacture: NEKO LIGHTING AG Type: FUSION Linear Syste

FUSION Linear System FL1800(R)F-WW1800-32W-940-BN

General

Indoor

- Linear System
- Trimless Recessed
- Version: square
- Housing: black
- Reflector: matte
- IP 20

LED

- 4000K
- CRI 90
- LED Output: 4400lm
- System Output: 2500lm
- 50000h@L80B10
- SDCM: 3

Optics

• Beam angle: Wall Washer

Electric

- LED Driver: ON-OFF
- LED Power: 32W
- System Power: 36W
- 46V • 700mA
- /00/11/

Dimensions

- Measurement: 1800mm x 50mm
- Cutout: 1810mm x 52mm
- Height: 95mm
- Ceiling height: 150mm



Light distribution

FUSION Linear profile with Wall Washer (WW1800) insert and ON-OFF driver as trimless recessed; black profile channel (RAL 9005) and matte reflector; LED 32W; measurement 1800mm x 50mm; CCT 4000K with an LED Output of 4400lm; high colour rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient SAMSUNG LED Chips; 5 years warranty; lighting perfectly suitable for a wide illumination of wall surfaces to allow homogeneous light distribution; degree of housing protection according to DIN EN 60529 (IP20)

WW600-11W-830 Diameter HeightEmax 0392 2m 96ix 0392 2m 96ix 0396 0 308 0396 0 308 0396 0 568 05

Technical drawing





C ENERG

CB CE Rohs

онз 🖒



1810x52mm

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.





