# **Datasheet**

# **FUSION FF1**

Manufacture: NEKO LIGHTING AG

**OSRAM** 

Type: FUSION Fixed Downlight FF1-8404002N-BS



#### General

- Indoor
- Downlight
- · Recessed mounted
- Version: square
- Housing: black
- Reflector: specular
- IP 20

#### **LED**

• 4000K

• CRI 80

• LED Output: 280lm

- System Output: 190lm
- 50000h@L80B10
- SDCM: 3

## Optics

- Beam angle: 40°
- UGR <10

# Electric

- LED Driver: noneLED Power: 2WSystem Power: 3W
- 3.5V
- 700mA


#### Dimensions

- Measurement: 45mm x 45mm
- Cutout: 37mm x 37mm
- · Height: 60mm
- Ceiling height: 120mm
- Net Weight: 95g
- Gross Weight: 140g


#### Description

Square recessed ceiling downlight made of die-cast aluminium with black powder-coating finish (RAL 9005) and specular reflector; LED 2W; measurement 45mm x 45mm; ceiling cutout of 37mm x 37mm with a narrow mounting trim; luminaire's weight is approximately 95g; CCT 4000K with an LED Output of 280lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; beam characteristic with 40° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<10); degree of housing protection according to DIN EN 60529 (IP20)

## Light distribution



## Technical drawing

















37x37mm















The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

