


Datasheet

FUSION FF1

Manufacture: NEKO LIGHTING AG

Type: FUSION Fixed Downlight FF1-9304002N-BS



General

- Indoor
- Downlight
- Recessed mounted
- Version: square
- Housing: black
- Reflector: specular
- IP 20

LED

- 3000K
- CRI 90
- LED Output: 220lm
- System Output: 140lm
- 50000h@L80B10
- SDCM: 3

OSRAM

Optics

- Beam angle: 40°
- UGR <10

Electric

- LED Driver: none
- LED Power: 2W
- System Power: 3W
- 3.5V
- 700mA


Dimensions

- Measurement: 45mm x 45mm
- Cutout: 37mm x 37mm
- Height: 60mm
- Ceiling height: 120mm
- Net Weight: 95g
- Gross Weight: 140g

Description

Square recessed ceiling downlight made of die-cast aluminium with black powder-coating finish (RAL 9005) and specular reflector; LED 2W; measurement 45mm x 45mm; ceiling cutout of 37mm x 37mm with a narrow mounting trim; luminaire's weight is approximately 95g; CCT 3000K with an LED Output of 220lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; beam characteristic with 40° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<10); degree of housing protection according to DIN EN 60529 (IP20)

Light distribution



Technical drawing



RoHS



37x37mm



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.