## **Datasheet**

# **FUSION FF1**

Manufacture: NEKO LIGHTING AG

**OSRAM** 

Type: FUSION Fixed Downlight FF1-9402402N-WB



#### General

- Indoor
- Downlight
- Recessed mounted
- Version: square
- Housing: white
- Reflector: black
- IP 20

#### **LED**

• 4000K

• CRI 90

LED Output: 250lmSystem Output: 160lm

• 50000h@L80B10

• SDCM: 3

#### Optics

• Beam angle: 24°

• UGR <10

#### Electric

LED Driver: noneLED Power: 2WSystem Power: 3W

• 3.5V • 700mA

#### Dimensions

• Measurement: 45mm x 45mm

• Cutout: 37mm x 37mm

· Height: 60mm

· Ceiling height: 120mm


• Net Weight: 95g

• Gross Weight: 140g


### Description

Square recessed ceiling downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and black reflector; LED 2W; measurement 45mm x 45mm; ceiling cutout of 37mm x 37mm with a narrow mounting trim; luminaire's weight is approximately 95g; CCT 4000K with an LED Output of 250lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; narrow beam characteristic with 24° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<10); degree of housing protection according to DIN EN 60529 (IP20)

#### Light distribution



#### **Technical drawing**

















37x37mm















The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

