# **Datasheet**

# **FUSION FF10**

Manufacture: NEKO LIGHTING AG

**OSRAM** 

Type: FUSION Fixed Downlight FF10-8272422N-WB

#### General

- Indoor
- Downlight
- · Recessed mounted
- Version: square
- Housing: white
- Reflector: black
- IP 20

#### **LED**

• 2700K

• 2700K • CRI 80

LED Output: 2400lmSystem Output: 1600lm

- 50000h@L80B10
- SDCM: 3

#### Optics

• Beam angle: 24°

• UGR <10

### Electric

LED Driver: noneLED Power: 22WSystem Power: 24W

• 31V

• 700mA

#### Dimensions

• Measurement: 290mm x 45mm

• Cutout: 282mm x 37mm

· Height: 60mm


• Ceiling height: 120mm

Net Weight: 530gGross Weight: 660g


## Description

Square recessed ceiling downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and black reflector; LED 22W; measurement 290mm x 45mm; ceiling cutout of 282mm x 37mm with a narrow mounting trim; luminaire's weight is approximately 530g; CCT 2700K with an LED Output of 2400lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; narrow beam characteristic with 24° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<10); degree of housing protection according to DIN EN 60529 (IP20)

#### Light distribution



#### **Technical drawing**

















282x37mm















The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

