# **FUSION FF10**

warming the state of the state

Manufacture: NEKO LIGHTING AG

Type: FUSION Fixed Downlight FFTA-8402422N-BB

#### General

- Indoor
- Downlight
- Recessed mountedVersion: trimless square
- Housing: black
- Reflector: black
- IP 20

#### **LED**

• 4000K **OSRAM** 

- CRI 80
- LED Output: 2800lmSystem Output: 2000lm
- 50000h@L80B10
- SDCM: 3

### Optics

- Beam angle: 24°
- UGR <10

## Electric

- LED Driver: noneLED Power: 22WSystem Power: 24W
- 31V • 700mA

#### Dimensions

• Measurement: 286.5mm x 41mm

• Cutout: 290mm x 44mm

· Height: 62.5mm

• Ceiling height: 120mm


• Net Weight: 850g

• Gross Weight: 980g


# Description

Square recessed ceiling downlight made of die-cast aluminium with black powder-coating finish (RAL 9005) and black reflector; LED 22W; measurement 286.5mm x 41mm; ceiling cutout of 290mm x 44mm with a trimless mounting; luminaire's weight is approximately 850g; CCT 4000K with an LED Output of 2800lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; narrow beam characteristic with 24° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<10); degree of housing protection according to DIN EN 60529 (IP20)

### Light distribution



#### **Technical drawing**

















290x44mm















The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

