Datasheet

FUSION FF3

Manufacture: NEKO LIGHTING AG

OSRAM

Type: FUSION Fixed Downlight FF3-9274007N-BS



General

- Indoor
- Downlight
- · Recessed mounted
- Version: square
- Housing: black
- Reflector: specular
- IP 20

LED

• 2700K

• CRI 90

• LED Output: 620lm

- System Output: 470lm
- 50000h@L80B10
- SDCM: 3

Optics

- Beam angle: 40°
- UGR <10

Electric

- LED Driver: noneLED Power: 7WSystem Power: 9W
- System Power: 9W
- 700mA

Dimensions

• Measurement: 98mm x 45mm

• Cutout: 90mm x 37mm

· Height: 60mm


Ceiling height: 120mmNet Weight: 180g

Gross Weight: 245g


Description

Square recessed ceiling downlight made of die-cast aluminium with black powder-coating finish (RAL 9005) and specular reflector; LED 7W; measurement 98mm x 45mm; ceiling cutout of 90mm x 37mm with a narrow mounting trim; luminaire's weight is approximately 180g; CCT 2700K with an LED Output of 620lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; beam characteristic with 40° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<10); degree of housing protection according to DIN EN 60529 (IP20)

Light distribution



Technical drawing

















90x37mm















The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

