### **Datasheet**

## **FUSION FG10**



Manufacture: NEKO LIGHTING AG

Type: FUSION General Downlight FGTA-8277522N-WB

#### General

- Indoor
- Downlight
- Recessed mounted
- Version: trimless square
- Housing: whiteReflector: black
- IP 20

#### \* IF 20

# LED OSRAM

- CRI 80
- LED Output: 2400lmSystem Output: 900lm
- 50000h@L80B10
- SDCM: 3

#### Optics

• Beam angle: 75°

• UGR <10

#### Electric

- LED Driver: noneLED Power: 22WSystem Power: 24W
- 31V • 700mA

#### Dimensions

• Measurement: 286.5mm x 41mm

• Cutout: 290mm x 44mm

· Height: 62.5mm

• Ceiling height: 120mm


• Net Weight: 800g

• Gross Weight: 930g


### Description

Square recessed ceiling downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and black reflector; LED 22W; measurement 286.5mm x 41mm; ceiling cutout of 290mm x 44mm with a trimless mounting; luminaire's weight is approximately 800g; CCT 2700K with an LED Output of 2400lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; wide beam characteristic with 75° beam angle; degree of housing protection according to DIN EN 60529 (IP20)

#### Light distribution



#### **Technical drawing**

































The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

