Datasheet

GAME 350

Manufacture: NEKO LIGHTING AG

GAME 350 Ceiling Light GASM-8279012F-WN-U Type:



General

- Indoor
- · Ceiling Light/Wall Light
- direct/indirect Version: round · Housing: white
- · Reflector: none
- IP 40

LED

• 2700K

OSRAM

• CRI 80

• LED Output: 1800lm/900lm · System Output: 1300lm/800lm

• 50000h@L80B10

• SDCM: 3

Optics

• Beam angle: 90°/110°

• UGR <19

Electric

• LED Driver: ON-OFF • LED Power: 12W/8W • System Power: 14W/10W

• 34V/33V • 350mA/250mA

Dimensions


• Measurement: Ø350mm

• Height: 78mm · Net Weight: 2800g · Gross Weight: 3500g

Description

Round Ceiling Light/Wall Light with microprismatic cover for lower luminance with uplight made of die-cast-aluminium with white powder-coating finish (RAL 9016); ON-OFF Driver; LED 12W+8W; measurement Ø350mm; luminaire's weight is approximately 2800g; CCT 2700K with an LED Output of 1800lm / 900lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; wide beam characteristic with 90° / 110° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP40)

Light distribution



Technical drawing

























The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

