Datasheet

GAME 350



Manufacture: NEKO LIGHTING AG GAME 350 Ceiling Light GASM-8409012P-WN

General

Type:

- Indoor
- Ceiling Light/Wall Light
- direct
- Version: round
- · Housing: white
- Reflector: none
- IP 40

LED

- 4000K
- CRI 80
- LED Output: 2000lm

OSRAM

- System Output: 1500lm
- 50000h@L80B10
- SDCM: 3

Optics

- Beam angle: 90°
- UGR <19

Electric

- LED Driver: Phase Dim
- LED Power: 12W
- System Power: 14W
- 34V
- 350mA


Dimensions

- Measurement: Ø350mm
- Height: 78mm
- Net Weight: 2200g
- Gross Weight: 2900g

Description

Round Ceiling Light/Wall Light with microprismatic cover for lower luminance made of diecast-aluminium with white powder-coating finish (RAL 9016); Phase Dim Driver; LED 12W; measurement Ø350mm; luminaire's weight is approximately 2200g; CCT 4000K with an LED Output of 2000lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; wide beam characteristic with 90° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP40)

Light distribution



Technical drawing





The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

