

# Datasheet

## GAME 900 Rod

Manufacture: NEKO LIGHTING AG

Type: GAME Ceiling Light GDPR-8409065D-WN-U



### General

- Indoor
- Pendant Light
- direct/indirect
- Version: round
- Housing: white
- Reflector: none
- IP 40

### LED

- 4000K
- CRI 80
- LED Output: 11000lm/2900lm
- System Output: 8400lm/2600lm
- 50000h@L80B10
- SDCM: 3

OSRAM

### Optics

- Beam angle: 90°/110°
- UGR <19

### Electric

- LED Driver: DALI Dim
- LED Power: 65W/25W
- System Power: 68W/28W
- 46V/36V
- 1400mA/700mA


### Dimensions

- Measurement: Ø900mm
- Height: 1096.5mm
- Net Weight: 11850g
- Gross Weight: 14950g


### Description

Round rod pendant luminaire with Uplight made of die-cast aluminium with white powder-coating finish (RAL 9016); DALI Dim Driver; LED 65W+25W; measurement Ø900mm; luminaire's weight is approximately 11850g; CCT 4000K with an LED Output of 11000lm / 2900lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; wide beam characteristic with 90° / 110° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP40)

### Light distribution



### Technical drawing



RoHS



Driver



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.