

MIU-P S

Manufacture: NEKO LIGHTING AG

Type: MIU Pendant Light MPS1-8271811F-WB



General

- Indoor
- Downlight
- Pendant installation
- Version: round
- Housing: white
- Reflector: black
- IP 20

LED

- 2700K
- CRI 80
- LED Output: 950lm
- System Output: 800lm
- 50000h@L80B10
- SDCM: 3



Optics

- Beam angle: 18°
- UGR <19

Electric

- LED Driver: ON-OFF
- LED Power: 9W
- System Power: 11W
- 36V
- 260mA


Dimensions

- Measurement: Ø55mm
- Height: 250mm
- Net Weight: 840g
- Gross Weight: 940g

Description

Round pendant light made of die-cast-aluminium with ON-OFF driver; white powder-coating finish (RAL 9016) and black reflector; LED 9W; measurement Ø55mm; luminaire's weight is approximately 840g; CCT 2700K with an LED Output of 950lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; narrow beam characteristic with 18° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP20)

Light distribution



Technical drawing



RoHS



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.