Datasheet

PURE Art

Manufacture: NEKO LIGHTING AG

Type: PURE Art Tracklight PUA2-8301815F-BB



General

- Indoor
- Tracklight
- Track mounted
- · Version: round
- · Housing: black
- Reflector: black
- IP 20

LED



• 3000K

• CRI 80 · LED Output: 1350lm

- System Output: 1050lm
- 50000h@L80B10
- SDCM: 3

Optics

• Beam angle: 18°

• UGR <19

Electric

• LED Driver: ON-OFF • LED Power: 13W • System Power: 15W

• 36V • 350mA

Dimensions

• Measurement: Ø55mm


· Height: 150mm · Net Weight: 700g • Gross Weight: 900g

• Pivot: max. 90° • Rotation: 355°


Description

Tracklight round made of die-cast aluminium with black powder-coating finish (RAL 9005) and black reflector; ON-OFF Driver; System Power 15W; measurements tracklight Ø55mm x 150mm; rotation 355° and pivot max. 90°; CCT 3000K with a System Luminous Flux of 1050lm; decent color rendering at an index of CRI80; after a lifetime of 50000h L80B10 min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 18° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work UGR<19; degree of housing protection IP20

Light distribution



Technical drawing























RG₁





The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

