## **Datasheet**

# **PURE S-C**

Manufacture: NEKO LIGHTING AG


Type: PURE S-C Ceiling Mounted Spotlight PUSC-8273015F-BB



#### General

- Indoor
- Spotlight
- Ceiling mounted
- Version: roundHousing: black
- Reflector: black
- IP 20

#### **LED**



- CRI 80
- LED Output: 1600lmSystem Output: 1300lm
- 50000h@L80B10
- SDCM: 3

### Optics

• Beam angle: 30°

• UGR <19

#### Electric

LED Driver: ON-OFFLED Power: 13WSystem Power: 15W

• 36V • 350mA

#### Dimensions


Measurement: Ø72mmHeight: 140mmNet Weight: 700gGross Weight: 900g

Pivot: 90°Rotation: 355°


#### Description

Ceiling mounted Spotlight round made of die-cast aluminium with black powder-coating finish (RAL 9005) and black reflector; ON-OFF Driver; System Power 15W; measurements spotlight Ø72mm x 140mm; rotation 355° and pivot max. 90°; CCT 2700K with a System Luminous Flux of 1300lm; decent color rendering at an index of CRI80; after a lifetime of 50000h L80B10 min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 30° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work UGR<19; degree of housing protection IP20; Can only be mounted in a false ceiling

#### Light distribution



#### **Technical drawing**























The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

