Datasheet

PURE S-C

Manufacture: NEKO LIGHTING AG

Type: PURE S-C Ceiling Mounted Spotlight PUSC-9272515P-WB



General

- Indoor
- Spotlight
- · Ceiling mounted
- Version: round
- · Housing: white
- · Reflector: black
- IP 20

LED



- 2700K • CRI 90
- LED Output: 1400lm
- System Output: 1100lm
- 50000h@L80B10
- SDCM: 3

Optics

• Beam angle: 25°

• UGR <19

Electric

• LED Driver: Phase Dim • LED Power: 13W • System Power: 15W

• 36V • 350mA

Dimensions


• Measurement: Ø72mm · Height: 140mm · Net Weight: 700g

• Pivot: 90° • Rotation: 355°


Description

Ceiling mounted Spotlight round made of die-cast aluminium with white powder-coating finish (RAL 9016) and black reflector; Phase Dim Driver; System Power 15W; measurements spotlight Ø72mm x 140mm; rotation 355° and pivot max. 90°; CCT 2700K with a System Luminous Flux of 1100lm; high color rendering at an index of CRI90; after a lifetime of 50000h L80B10 min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 25° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work UGR<19; degree of housing protection IP20; Can only be mounted in a false ceiling

Light distribution



Technical drawing



















• Gross Weight: 900g

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

