

# Datasheet

## PURE S



Manufacture: NEKO LIGHTING AG

Type: PURE S Tracklight PUS1-9302515P-WB

### General

- Indoor
- Tracklight
- Tracklight
- Version: round
- Housing: white
- Reflector: black
- System Output: 1200lm
- IP 20

### LED

- 3000K
- CRI90
- 1500lm
- 50000h@L80B10
- SDCM: 3

### Optics

- Beam angle: 25°
- UGR <19

### Electric

- LED Driver: Phase Dim
- LED Power: 13W
- System Power: 15W
- 36V
- 350mA

### Dimensions


- Measurement: Ø72mm
- Height: 140mm
- Net Weight: 700g
- Gross Weight: 900g
- Pivot: max. 90°
- Rotation: 355°

### Description


Tracklight round made of die-cast aluminium with white powder-coating finish (RAL 9016) and black reflector; LED 13W; measurement Ø72mm; tracklights length 140mm; luminaire's weight is approximately 700g; rotation 355° and pivot max. 90°; CCT 3000K with an LED Output of 1500lm; with Phase Dim Driver; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 25° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP20)



### Light distribution



### Technical drawing



RoHS



Driver

GLOBAL

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.