Datasheet

SUGAR 350

Manufacture: NEKO LIGHTING AG

Type: SUGAR 350 Ceiling Light SASM-8409012D-BG

General

- Indoor
- · Ceiling Light/Wall Light
- direct
- Version: round · Housing: black · Reflector: gold
- IP 40

LED

• 4000K

- CRI 80
- · LED Output: 2000lm • System Output: 1500lm
- 50000h@L80B10
- SDCM: 3

Optics

- Beam angle: 90°
- UGR <19

Electric

• LED Driver: DALI Dim • LED Power: 12W • System Power: 14W

• 34V • 350mA

Dimensions


• Measurement: Ø350mm

· Height: 103mm · Net Weight: 2400g


Description

Round Ceiling Light/Wall Light with microprismatic cover for lower luminance made of diecast-aluminium with black powder-coating finish (RAL 9005) and gold decoration ring; DALI Dim Driver; LED 12W; measurement Ø350mm; luminaire's weight is approximately 2400g; CCT 4000K with an LED Output of 2000lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; wide beam characteristic with 90° beam angle; luminaireing perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP40)

Light distribution



Technical drawing



















OSRAM

• Gross Weight: 3000g







The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

