Datasheet

SUGAR 350



Manufacture: NEKO LIGHTING AG
Type: SUGAR 350 Ceiling Light SASM-9309012F-WW

General

- Indoor
- Ceiling Light/Wall Light
- direct
- Version: round
- Housing: white
- Reflector: white
- IP 40

LED

- 3000K
- CRI 90
- LED Output: 1700lm
- System Output: 1200lm
- 50000h@L80B10
- SDCM: 3

Optics

- Beam angle: 90°
- UGR <19

Electric

- LED Driver: ON-OFF
- LED Power: 12W
- System Power: 14W
- 34V
- 350mA


Dimensions

- Measurement: Ø350mm
- Height: 103mm
- Net Weight: 2400g
- Gross Weight: 3000g


Description

Round Ceiling Light/Wall Light with microprismatic cover for lower luminance made of die-cast-aluminium with white powder-coating finish (RAL 9016) and white decoration ring; ON-OFF Driver; LED 12W; measurement Ø350mm; luminaire's weight is approximately 2400g; CCT 3000K with an LED Output of 1700lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; wide beam characteristic with 90° beam angle; luminaireing perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP40)

Light distribution



Technical drawing



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.