Datasheet

SUGAR 350

Manufacture: NEKO LIGHTING AG

OSRAM

Type: SUGAR 350 Ceiling Light SASM-9409012F-WG

General

- Indoor
- · Ceiling Light/Wall Light
- direct
- Version: roundHousing: whiteReflector: gold
- IP 40

LED

• 4000K

• CRI 90

LED Output: 1800lmSystem Output: 1300lm50000h@L80B10

• SDCM: 3

Optics

Beam angle: 90°UGR <19

Electric

LED Driver: ON-OFFLED Power: 12WSystem Power: 14W

• 34V • 350mA

Dimensions


• Measurement: Ø350mm

Height: 103mmNet Weight: 2400gGross Weight: 3000g


Description

Round Ceiling Light/Wall Light with microprismatic cover for lower luminance made of die-cast-aluminium with white powder-coating finish (RAL 9016) and gold decoration ring; ON-OFF Driver; LED 12W; measurement Ø350mm; luminaire's weight is approximately 2400g; CCT 4000K with an LED Output of 1800lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; wide beam characteristic with 90° beam angle; luminaireing perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP40)

Light distribution



Technical drawing

























The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

