# Datasheet

# **TAKEO T100**

Manufacture:NEKO LIGHTING AGType:TAKEO Fixed Downlight TS2-9273013N-WM



#### General

#### • Indoor

- Downlight
- Fixed
- Recessed
- Version: round
- Housing: white
- Reflector: matt
- IP 54

#### LED

## 

### • 2700K

- CRI 90
- LED Output: 1400lm
- System Output: 1200lm
- 50000h@L80B10
- SDCM: 3

#### Optics

- Beam angle: 30°
- UGR <19

#### Electric

- LED Driver: none
- LED Power: 13W
- System Power: 15W
- 36V
- 350mA


#### Dimensions

- Measurement: Ø110mm
- Cutout: Ø100mm
- Height: 79mm
- Ceiling height: 130mm
- Net Weight: 420g
- Gross Weight: 520g


#### Description

Round recessed downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and matt reflector; LED 13W; measurement Ø110mm; narrow mounting trim with a cutout of Ø100mm; luminaire's weight is approximately 420g; CCT 2700K with an LED Output of 1400lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic wit 30° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP54)

#### Light distribution



#### **Technical drawing**





The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

