## **Datasheet**

# TAKEO T100

Manufacture: NEKO LIGHTING AG

Type: TAKEO Fixed Downlight TS2-9305013N-WM



#### General

- Indoor
- Downlight
- Fixed
- Recessed
- · Version: round
- Housing: white
- · Reflector: matt
- IP 54

#### **LED**



• 3000K

• CRI 90

LED Output: 1500lmSystem Output: 1100lm

• 50000h@L80B10

• SDCM: 3

#### Optics

Beam angle: 50°UGR <19</li>

#### Electric

LED Driver: noneLED Power: 13WSystem Power: 15W

• 36V • 350mA

#### **Dimensions**

• Measurement: Ø110mm

• Cutout: Ø100mm

• Height: 79mm

• Ceiling height: 130mm


• Net Weight: 420g

• Gross Weight: 520g


### Description

Round recessed downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and matt reflector; LED 13W; measurement Ø110mm; narrow mounting trim with a cutout of Ø100mm; luminaire's weight is approximately 420g; CCT 3000K with an LED Output of 1500lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic wit 50° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP54)

#### Light distribution



#### **Technical drawing**

















Ø100mm











850°C



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

