Datasheet

TAKEO T200

Manufacture:NEKO LIGHTING AGType:TAKEO Fixed Downlight TL1-9303025N-BW



General

Indoor

- Downlight
- Recessed mounted
- Version: round
- Housing: black
- Reflector: white
- IP 54

LED

• 3000K

- CRI 90
- LED Output: 3200lm
- System Output: 2800lm
- 50000h@L80B10
- SDCM: 3

Optics

• Beam angle: 30°

Electric

- LED Driver: none
- LED Power: 25W
- System Power: 28W
- 36V
- 700mA


Dimensions

- Measurement: Ø218mm
- Cutout: Ø200mm
- Height: 132mm
- Ceiling height: 180mm
- Net Weight: 1700g
- Gross Weight: 2000g


Description

Round recessed mounted Downlight made of die-cast aluminium with black powder-coating finish (RAL 9005) and white reflector; LED 25W; measurement Ø218mm; narrow mounting trim with a cutout of Ø200mm; luminaire's weight is approximately 1700g; CCT 3000K with an LED Output of 3200lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 30° beam angle; degree of housing protection according to DIN EN 60529 (IP54)

Light distribution



Technical drawing





The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.



CITIZEN Micro Humantech Light