Datasheet

TAKEO T200

Manufacture: NEKO LIGHTING AG

Type: TAKEO Fixed Downlight TL3-8406052N-WM



General

- Indoor
- Downlight
- · Recessed mounted
- Version: round
- Housing: white
- Reflector: matt
- IP 54

LED



- CRI 80
- LED Output: 6800lm
- System Output: 5000lm
- 50000h@L80B10
- SDCM: 3

Optics

- Beam angle: 60°
- UGR <19

Electric

- LED Driver: noneLED Power: 52W
- System Power: 56W
- 36V
- 1400mA

Dimensions

• Measurement: Ø218mm


• Cutout: Ø200mm • Height: 132mm

Ceiling height: 180mmNet Weight: 1700gGross Weight: 2000g


Description

Round recessed mounted Downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and matt reflector; LED 52W; measurement Ø218mm; narrow mounting trim with a cutout of Ø200mm; luminaire's weight is approximately 1700g; CCT 4000K with an LED Output of 6800lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 60° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP54)

Light distribution



Technical drawing

















Ø200mm











850°C



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

