Datasheet

TAKEO T75

Manufacture:NEKO LIGHTING AGType:TAKEO Fixed Downlight TT2-8402511N-WW



General

Indoor

- Downlight
- Recessed mounted
- Version: round
- Housing: white
- Reflector: white
- IP 54

LED

• 4000K

- CRI 80
- LED Output: 1500lm
- System Output: 1050lm
- 50000h@L80B10
- SDCM: 3

Optics

• Beam angle: 25°

Electric

- LED Driver: none
- LED Power: 11W
- System Power: 13W
- 31V
- 350mA


Dimensions

- Measurement: Ø84mm
- Cutout: Ø75mm
- Height: 72mm
- Ceiling height: 122mm
- Net Weight: 280g
- Gross Weight: 340g


Description


Round recessed mounted downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and white reflector; LED 11W; measurement Ø84mm; narrow mounting trim with a cutout of Ø75mm; luminaire's weight is approximately 280g; CCT 4000K with an LED Output of 1500lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 25° beam angle; degree of housing protection according to DIN EN 60529 (IP54)

Light distribution



Technical drawing





The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.



CITIZEN