# **Datasheet**

# **TAKEO TS200**

Manufacture: NEKO LIGHTING AG

CITIZEN

Type: TAKEO Fixed Downlight TSL2-8277038N-WB



#### General

- Indoor
- Downlight
- Recessed mounted
- Version: square
- Housing: white
- Reflector: black
- IP 54

#### **LED**



• CRI 80

LED Output: 5200lmSystem Output: 3000lm

• 50000h@L80B10

• SDCM: 3

# Optics

• Beam angle: 70°

• UGR <19

#### Electric

LED Driver: noneLED Power: 38WSystem Power: 42W

• 36V

• 1050mA

#### Dimensions

• Measurement: 220mm x 220mm


• Cutout: 200mm x 200mm

Height: 132mmCeiling height: 180mmNet Weight: 1500gGross Weight: 1800g


### Description

Square recessed mounted Downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and black reflector; LED 38W; measurement 220mm x 220mm; narrow mounting trim with a cutout of 200mm x 200mm; luminaire's weight is approximately 1500g; CCT 2700K with an LED Output of 5200lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 70° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP54)

# Light distribution



# **Technical drawing**

















200x200mm











850°C



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

