## **Datasheet**

# **TAKEO TS200**

Manufacture: NEKO LIGHTING AG

Type: TAKEO Fixed Downlight TSL2-9307038N-WM



#### General

- Indoor
- Downlight
- · Recessed mounted
- Version: square
- · Housing: white
- Reflector: matt
- IP 54

#### **LED**



- CRI 90
- LED Output: 4600lm
- System Output: 2700lm
- 50000h@L80B10
- SDCM: 3

#### Optics

- Beam angle: 70°
- UGR <19

#### Electric

- LED Driver: none
  LED Power: 38W
- System Power: 42W36V
- 1050mA

#### Dimensions

• Measurement: 220mm x 220mm


• Cutout: 200mm x 200mm

Height: 132mm Ceiling height: 180mm Net Weight: 1500g Gross Weight: 1800g


### Description

Square recessed mounted Downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and matt reflector; LED 38W; measurement 220mm x 220mm; narrow mounting trim with a cutout of 200mm x 200mm; luminaire's weight is approximately 1500g; CCT 3000K with an LED Output of 4600lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 70° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP54)

#### Light distribution



#### **Technical drawing**

















200x200mm











850°C



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

