Datasheet

TAKEO TS200

Manufacture: NEKO LIGHTING AG

CITIZEN

Type: TAKEO Fixed Downlight TSL2-9407038N-WB



General

- Indoor
- Downlight
- Recessed mounted
- Version: square
- · Housing: white
- Reflector: black
- IP 54

LED





• LED Output: 4800lm

- System Output: 2900lm50000h@L80B10
- SDCM: 3

Optics

• Beam angle: 70°

• UGR <19

Electric

LED Driver: noneLED Power: 38WSystem Power: 42W

• 36V

• 1050mA

Dimensions

• Measurement: 220mm x 220mm

• Cutout: 200mm x 200mm


Height: 132mmCeiling height: 180mm

Net Weight: 1500gGross Weight: 1800g


Description

Square recessed mounted Downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and black reflector; LED 38W; measurement 220mm x 220mm; narrow mounting trim with a cutout of 200mm x 200mm; luminaire's weight is approximately 1500g; CCT 4000K with an LED Output of 4800lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 70° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP54)

Light distribution



Technical drawing

















200x200mm











850°C



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

