







NEKO / FUSION / FF2
Fixed LED Downlight



4W | CR190 | 2700K | 24° | CREE | UGR < 10 | IP 20 | 5 YEARS GUARANTEE | CB | CE | UL LISTED



	LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code							
 Black Reflector	4 W	6 W	6.5 V	700 mA	80	2700K	24°	450lm	330lm	FF2-8272404 X-WB							
							40°	450lm	330lm	FF2-8274004 X-WB							
							3000K	24°	500lm	350lm	FF2-8302404 X-WB						
								40°	500lm	350lm	FF2-8304004 X-WB						
							4000K	24°	550lm	380lm	FF2-8402404 X-WB						
								40°	550lm	380lm	FF2-8404004 X-WB						
							 Black Reflector	4 W	6 W	6.5 V	700 mA	80	2700K	24°	450lm	330lm	FF2-8272404 X-BB
														40°	450lm	330lm	FF2-8274004 X-BB
3000K	24°	500lm	350lm	FF2-8302404 X-BB													
	40°	500lm	350lm	FF2-8304004 X-BB													
4000K	24°	550lm	380lm	FF2-8402404 X-BB													
	40°	550lm	380lm	FF2-8404004 X-BB													
 Specular Reflector	4 W	6 W	6.5 V	700 mA	80	2700K								24°	450lm	380lm	FF2-8272404 X-WS
														40°	450lm	380lm	FF2-8274004 X-WS
							3000K	24°	500lm	400lm	FF2-8302404 X-WS						
								40°	500lm	400lm	FF2-8304004 X-WS						
							4000K	24°	550lm	440lm	FF2-8402404 X-WS						
								40°	550lm	440lm	FF2-8404004 X-WS						
							 Specular Reflector	4 W	6 W	6.5 V	700 mA	80	2700K	24°	450lm	380lm	FF2-8272404 X-BS
														40°	450lm	380lm	FF2-8274004 X-BS
3000K	24°	500lm	400lm	FF2-8302404 X-BS													
	40°	500lm	400lm	FF2-8304004 X-BS													
4000K	24°	550lm	440lm	FF2-8402404 X-BS													
	40°	550lm	440lm	FF2-8404004 X-BS													

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)