




Product Service

Attestation of Conformity

No. N8A 16 08 90185 017

Holder of Certificate: NEKO Lighting AGKreuzstrasse 2
8008 Zürich
SWITZERLAND**Product: Recessed luminaires
(LED DOWNLIGHT)****Model(s):** S100xyz; S100xy3; S125xyz; S125xy3; S150xyz; S150xy3;
A100-18W; TA123-13W; TA123-18W; TF174-18W; TF174-26W;
TA174-26W; TA174-38W
(See page 2 for details of model description)**Parameters:**
Rated Voltage : 220-240VDC
Rated Frequency : 50/60Hz
Rated Power : See page 2 for details
Protection Class : II
Degree of Protection : IP20
Lamp Classification : Exempt group
ta : 40°C**Tested according to:** EN 60598-2-2:2012
EN 60598-1:2015
EN 62471:2008
EN 62493:2015

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 681401624901**Date,** 2016-08-17
(Taylor Yao)**CE** After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

Page 1 of 2



Attestation of Conformity
No. N8A 16 08 90185 017

Model No.	Rated Power (W)
S100xyz	15
S100xy3	15
S125xyz	21
S125xy3	21
S150xyz	28
S150xy3	28
A100-18W	21
TA123-13W	16
TA123-18W	21
TF174-18W	22
TF174-26W	30
TA174-26W	30
TA174-38W	42
Remark: "x" can be "R" or "S", stands for shape of lamp cover, R=Round cover, S=Square cover; "y" can be "T" or blank, stands for different accessories, T=Trimless, blank=Standard; "z" can be "1" or "2", stands for adjustability of lamp cover, 1=Adjustable, 2=Fixed.	