

LED Downlight SENSE Series S100R2-13W-DW-918-M



Light Output Ratio:	100.0%	
Luminaire Power:	0.3626 W	
SHR Nominal:	0.50	Calculated using the TM5
SHR Maximum:	0.65	fine grid method.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Jason
Test Date: 2021-01-19


γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity: 58%
Test Distance: 8.967m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:25.90V I:0.0140A P:0.3626W PF:1.000 Freq:0Hz Lamp Flux:14.2982x1 lm		
NAME: S100R2-13W-DW-918-M	TYPE:Downlight	SERIAL No.:
SPEC.:1800K	DIM.: ϕ 108mm*H126mm	
MFR.: NEKO LIGHTING AG		

DATA OF LAMP		PHOTOMETRIC DATA Eff: 39.43 lm/W			
MODEL	BRIDGELUX-1800K	I _{max} (cd)	25.34	S/MH (C0/180)	0.51
NOMINAL POWER (W)	13	LOR (%)	100.0	S/MH (C90/270)	0.61
RATED VOLTAGE (V)	26	TOTAL FLUX (lm)	14.298	η UP,DN (C0-180)	0.0,52.6
NOMINAL FLUX (lm)	14.2982	CIE CLASS	DIRECT	η UP,DN (C180-360)	0.0,47.4
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE (V)	25.9	η down (%)	100.0	CIBSE SHR MAX	0.65

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	24.62	24.17	21.47	18.61	18.25	18.71	20.99	23.32	0- 10	2.173	2.173	15.2,15.2
20	19.03	18.26	12.39	7.760	6.988	7.447	11.18	16.61	10- 20	4.712	6.884	48.1,48.1
30	8.539	7.263	3.946	2.367	2.130	2.319	3.505	6.516	20- 30	3.648	10.53	73.7,73.7
40	2.783	2.335	1.568	1.150	1.099	1.193	1.453	2.221	30- 40	1.762	12.29	86,86
50	1.265	1.130	0.9609	0.6880	0.6568	0.7455	0.8575	1.151	40- 50	0.9750	13.27	92.8,92.8
60	0.7710	0.6775	0.5193	0.2823	0.2564	0.3341	0.4106	0.6990	50- 60	0.6265	13.90	97.2,97.2
70	0.3446	0.2670	0.2007	0.0255	0.0050	0.0771	0.1127	0.2981	60- 70	0.3143	14.21	99.4,99.4
80	0.0824	0.0204	0.0002	0	0	0	0	0.0567	70- 80	0.0838	14.29	100,100
90	0	0	0	0	0	0	0	0	80- 90	0.0041	14.30	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 12.835 lm

%lum = 89.8%

%lamp = 89.8%

Conical surface Flux(120deg): 13.896 lm

%lum = 97.2%


%lamp = 97.2%

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:25.90V I:0.0140A P:0.3626W PF:1.000 Freq:0Hz Lamp Flux:14.2982x1 lm		
NAME: S100R2-13W-DW-918-M	TYPE:Downlight	SERIAL No.:
SPEC.:1800K	DIM.: ϕ 108mm*H126mm	
MFR.: NEKO LIGHTING AG		



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	0	0
80	52	0
75	80	35
70	110	64
65	137	90
60	168	113
55	188	143
50	215	163
45	275	183


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:25.90V I:0.0140A P:0.3626W PF:1.000 Freq:0Hz Lamp Flux:14.2982x1 lm		
NAME: S100R2-13W-DW-918-M	TYPE:Downlight	SERIAL No.:
SPEC.:1800K	DIM.: ϕ 108mm*H126mm	
MFR.: NEKO LIGHTING AG		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.11	1.08	1.06	1.08	1.06	1.04	1.04	1.03	1.01	1.01	.99	.98	.97	.96	.95	.93
2.0	1.03	.99	.95	1.01	.97	.94	.98	.95	.92	.95	.92	.90	.92	.90	.88	.87
3.0	.96	.91	.87	.94	.90	.86	.92	.88	.85	.89	.86	.83	.87	.84	.82	.81
4.0	.90	.84	.80	.89	.83	.79	.86	.82	.79	.84	.81	.78	.83	.79	.77	.75
5.0	.84	.79	.74	.83	.78	.74	.82	.77	.73	.80	.76	.73	.78	.75	.72	.70
6.0	.79	.74	.69	.79	.73	.69	.77	.72	.69	.76	.71	.68	.74	.71	.68	.66
7.0	.75	.69	.65	.74	.69	.65	.73	.68	.65	.72	.68	.64	.71	.67	.64	.63
8.0	.71	.65	.61	.71	.65	.61	.70	.65	.61	.69	.64	.61	.68	.64	.61	.59
9.0	.68	.62	.58	.67	.62	.58	.66	.61	.58	.65	.61	.58	.65	.61	.58	.56
10.0	.65	.59	.55	.64	.59	.55	.63	.58	.55	.63	.58	.55	.62	.58	.55	.54



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:25.90V I:0.0140A P:0.3626W PF:1.000 Freq:0Hz Lamp Flux:14.2982x1 lm		
NAME: S100R2-13W-DW-918-M	TYPE:Downlight	SERIAL No.:
SPEC.:1800K	DIM.: ϕ 108mm*H126mm	
MFR.: NEKO LIGHTING AG		

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.181	.103	.033	.175	.100	.032	.162	.093	.030	.150	.087	.028	.140	.081	.026		
2.0	.174	.095	.029	.168	.093	.029	.157	.087	.027	.148	.083	.026	.138	.078	.025		
3.0	.165	.088	.026	.160	.086	.026	.151	.082	.025	.142	.078	.024	.134	.074	.023		
4.0	.156	.081	.024	.151	.079	.023	.144	.076	.023	.136	.073	.022	.130	.070	.021		
5.0	.147	.075	.022	.144	.074	.021	.137	.071	.021	.130	.069	.020	.125	.067	.020		
6.0	.140	.070	.020	.136	.069	.020	.130	.067	.019	.125	.065	.019	.120	.063	.019		
7.0	.133	.066	.019	.130	.065	.018	.124	.063	.018	.120	.061	.018	.115	.060	.018		
8.0	.126	.062	.017	.124	.061	.017	.119	.059	.017	.115	.058	.017	.110	.057	.017		
9.0	.120	.058	.016	.118	.058	.016	.114	.056	.016	.110	.055	.016	.106	.054	.016		
10.0	.115	.055	.015	.113	.055	.015	.109	.053	.015	.106	.052	.015	.102	.051	.015		

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.171	.157	.145	.147	.135	.124	.100	.093	.086	.058	.054	.050	.018	.017	.016	
2.0	.156	.132	.112	.134	.114	.097	.092	.079	.068	.053	.046	.040	.017	.015	.013	
3.0	.144	.114	.089	.124	.098	.077	.085	.068	.054	.049	.040	.032	.016	.013	.010	
4.0	.134	.099	.072	.115	.085	.063	.079	.060	.044	.046	.035	.026	.015	.011	.009	
5.0	.125	.087	.060	.107	.076	.052	.074	.053	.037	.043	.031	.022	.014	.010	.007	
6.0	.117	.078	.050	.101	.068	.043	.069	.047	.031	.040	.028	.018	.013	.009	.006	
7.0	.110	.070	.042	.095	.061	.037	.066	.043	.026	.038	.025	.016	.012	.008	.005	
8.0	.104	.064	.036	.090	.056	.032	.062	.039	.022	.036	.023	.013	.012	.008	.004	
9.0	.099	.059	.032	.085	.051	.028	.059	.036	.020	.034	.021	.012	.011	.007	.004	
10.0	.094	.054	.028	.081	.047	.024	.056	.033	.017	.033	.020	.010	.011	.006	.003	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:25.90V I:0.0140A P:0.3626W PF:1.000 Freq:0Hz Lamp Flux:14.2982x1 lm										
NAME: S100R2-13W-DW-918-M					TYPE:Downlight			SERIAL No.:		
SPEC.:1800K					DIM.: ϕ 108mm*H126mm					
MFR.: NEKO LIGHTING AG										
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	19.9	20.9	20.2	21.1	21.2	17.9	18.8	18.1	19.0	19.2
3H	20.4	21.3	20.7	21.5	21.7	18.2	19.1	18.5	19.3	19.5
4H	20.5	21.4	20.8	21.6	21.8	18.2	19.0	18.5	19.3	19.5
6H	20.5	21.3	20.8	21.5	21.8	18.1	18.9	18.4	19.2	19.4
8H	20.5	21.2	20.8	21.5	21.8	18.1	18.8	18.4	19.1	19.4
12H	20.4	21.2	20.8	21.4	21.7	18.0	18.8	18.4	19.0	19.3
4H 2H	20.1	20.9	20.3	21.1	21.3	18.3	19.1	18.5	19.3	19.5
3H	20.7	21.4	21.0	21.7	21.9	18.7	19.5	19.1	19.7	20.0
4H	20.8	21.5	21.2	21.8	22.1	18.8	19.4	19.1	19.7	20.0
6H	20.8	21.4	21.2	21.8	22.1	18.7	19.3	19.1	19.6	19.9
8H	20.8	21.3	21.2	21.7	22.1	18.6	19.2	19.0	19.5	19.9
12H	20.8	21.2	21.2	21.6	22.0	18.6	19.1	19.0	19.4	19.8
8H 4H	20.8	21.3	21.2	21.7	22.0	18.8	19.3	19.2	19.7	20.0
6H	20.8	21.2	21.2	21.6	22.1	18.7	19.2	19.1	19.5	20.0
8H	20.8	21.2	21.2	21.6	22.0	18.7	19.0	19.1	19.5	19.9
12H	20.7	21.0	21.2	21.5	22.0	18.6	18.9	19.1	19.4	19.8
12H 4H	20.7	21.2	21.1	21.6	22.0	18.8	19.2	19.2	19.6	20.0
6H	20.8	21.1	21.2	21.6	22.0	18.7	19.1	19.1	19.5	19.9
8H	20.7	21.1	21.2	21.5	22.0	18.6	18.9	19.1	19.4	19.9
Variations with the observer position at spacings:										
S = 1.0H	+ 1.0 / - 1.2					+ 0.8 / - 1.0				
1.5H	+ 1.9 / - 1.1					+ 0.8 / - 0.7				
2.0H	+ 1.4 / - 1.1					+ 0.7 / - 1.4				

CIE Pub.117, 14.30 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = -14.8$)

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:25.90V I:0.0140A P:0.3626W PF:1.000 Freq:0Hz Lamp Flux:14.2982x1 lm		
NAME: S100R2-13W-DW-918-M	TYPE:Downlight	SERIAL No.:
SPEC.:1800K	DIM.: ϕ 108mm*H126mm	
MFR.: NEKO LIGHTING AG		


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	83	75	71	82	75	71	81	75	71	67
0.80	91	84	80	90	84	80	89	83	79	75
1.00	96	90	85	95	89	85	93	89	85	80
1.25	100	95	91	99	94	90	97	93	89	85
1.50	104	98	94	102	97	94	100	96	93	88
2.00	107	102	99	105	101	98	103	99	96	91
2.50	109	105	101	107	103	100	104	101	98	92
3.00	111	107	104	109	105	103	105	103	100	94
4.00	113	110	107	111	108	106	107	105	103	96
5.00	114	112	110	112	110	108	108	106	105	97
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Jason
 Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:58%
 Test Distance:8.967m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:25.90V I:0.0140A P:0.3626W PF:1.000 Freq:0Hz Lamp Flux:14.2982x1 lm		
NAME: S100R2-13W-DW-918-M	TYPE:Downlight	SERIAL No.:
SPEC.:1800K	DIM.: ϕ 108mm*H126mm	
MFR.: NEKO LIGHTING AG		




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

AAI Figure

Test:U:25.90V I:0.0140A P:0.3626W PF:1.000 Freq:0Hz Lamp Flux:14.2982x1 lm		
NAME: S100R2-13W-DW-918-M	TYPE:Downlight	SERIAL No.:
SPEC.:1800K	DIM.: ϕ 108mm*H126mm	
MFR.: NEKO LIGHTING AG		




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:25.90V I:0.0140A P:0.3626W PF:1.000 Freq:0Hz Lamp Flux:14.2982x1 lm		
NAME: S100R2-13W-DW-918-M	TYPE:Downlight	SERIAL No.:
SPEC.:1800K	DIM.: ϕ 108mm*H126mm	
MFR.: NEKO LIGHTING AG		



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:25.90V I:0.0140A P:0.3626W PF:1.000 Freq:0Hz Lamp Flux:14.2982x1 lm		
NAME: S100R2-13W-DW-918-M	TYPE:Downlight	SERIAL No.:
SPEC.:1800K	DIM.: ϕ 108mm*H126mm	
MFR.: NEKO LIGHTING AG		


AvgL	cd/m2
L_0~180 (65) av	83
L_0~180 (75) av	40
L_0~180 (85) av	0
L_90~270 (65) av	76
L_90~270 (75) av	17
L_90~270 (85) av	0
L_45 (65) av	81
L_45 (75) av	31
L_45 (85) av	0

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Jason
Test Date: 2021-01-19

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity: 58%
Test Distance: 8.967m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:8.967m [K=1.0000]
Remarks:

```