


Low Voltage Track System Module ML26-PS55-14W-930-36



Light Output Ratio:	100.0%	
Luminaire Power:	13.87 W	
SHR Nominal:	0.50	Calculated using the TM5
SHR Maximum:	0.50	fine grid method.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Jason
Test Date: 2020-05-08


γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity: 58%
Test Distance: 5.850m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:48.00V I:0.2889A P:13.87W PF:1.000 Freq:0Hz Lamp Flux:931.938x1 lm		
NAME: ML26-PS55-14W-930-36	TYPE:Low Voltage Track System Module	
SPEC.:3000K	DIM.: \varnothing 55mm*H180mm	
MFR.: NEKO LIGHTING AG		

DATA OF LAMP		PHOTOMETRIC DATA Eff: 67.21 lm/W			
MODEL	CITIZEN-3000K	I _{max} (cd)	2952	S/MH (C0/180)	0.53
NOMINAL POWER (W)	14	LOR (%)	100.0	S/MH (C90/270)	0.45
RATED VOLTAGE (V)	48	TOTAL FLUX (lm)	931.94	η UP, DN (C0-180)	0.0, 54.3
NOMINAL FLUX (lm)	931.938	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 45.7
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE (V)	48	η down (%)	100.0	CIBSE SHR MAX	0.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Jason
 Test Date: 2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity: 58%
 Test Distance: 5.850m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	2313	2450	2501	2472	2458	2357	2271	2239	0- 10	254.6	254.6	27.3, 27.3
20	755.2	936.8	1058	1088	990.4	720.2	537.4	568.9	10- 20	438.4	692.9	74.4, 74.4
30	144.8	175.6	162.4	161.4	173.2	142.1	122.0	122.7	20- 30	170.2	863.2	92.6, 92.6
40	39.31	48.88	49.09	47.27	47.25	39.10	32.21	32.24	30- 40	52.16	915.3	98.2, 98.2
50	5.802	7.570	7.489	7.119	7.093	5.167	4.065	4.288	40- 50	13.86	929.2	99.7, 99.7
60	0.6182	1.067	0.9838	0.9543	0.9266	0.5415	0.3919	0.4204	50- 60	2.454	931.6	100, 100
70	0.0745	0.0481	0.0787	0.0612	0.0569	0.0678	0.0370	0.0612	60- 70	0.2214	931.9	100, 100
80	0.0460	0.0350	0.0459	0.0371	0.0285	0.0372	0.0262	0.0371	70- 80	0.0478	931.9	100, 100
90	0.0395	0.0350	0.0371	0.0371	0.0241	0.0263	0.0262	0.0262	80- 90	0.0370	931.9	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 925.34 lm

%lum = 99.3%

%lamp = 99.3%

Conical surface Flux(120deg): 931.63 lm

%lum = 100.0%


%lamp = 100.0%

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Jason
Test Date: 2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity: 58%
Test Distance: 5.850m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.2889A P:13.87W PF:1.000 Freq:0Hz Lamp Flux:931.938x1 lm		
NAME: ML26-PS55-14W-930-36	TYPE:Low Voltage Track System Module	
SPEC.:3000K	DIM.: $\phi 55\text{mm} \times \text{H}180\text{mm}$	
MFR.: NEKO LIGHTING AG		



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	203	203
80	113	113
75	94	94
70	93	98
65	135	206
60	525	839
55	1790	2349
50	3835	4968
45	7581	12502


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:5.850m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.2889A P:13.87W PF:1.000 Freq:0Hz Lamp Flux:931.938x1 lm		
NAME: ML26-PS55-14W-930-36	TYPE:Low Voltage Track System Module	
SPEC.:3000K	DIM.: $\phi 55\text{mm} \times \text{H}180\text{mm}$	
MFR.: NEKO LIGHTING AG		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.13	1.11	1.09	1.10	1.09	1.07	1.06	1.05	1.04	1.03	1.02	1.01	.99	.99	.98	.96
2.0	1.07	1.04	1.01	1.05	1.02	.00	1.02	.00	.98	.99	.97	.96	.97	.95	.94	.92
3.0	1.02	.98	.95	1.01	.97	.94	.98	.95	.93	.96	.93	.91	.94	.92	.90	.89
4.0	.97	.93	.90	.96	.92	.89	.94	.91	.88	.93	.90	.87	.91	.88	.87	.85
5.0	.93	.89	.86	.93	.88	.85	.91	.87	.85	.89	.86	.84	.88	.85	.83	.82
6.0	.90	.85	.82	.89	.85	.82	.88	.84	.81	.86	.83	.81	.85	.82	.80	.79
7.0	.86	.82	.79	.86	.82	.79	.85	.81	.78	.84	.80	.78	.83	.80	.77	.76
8.0	.83	.79	.76	.83	.79	.76	.82	.78	.75	.81	.78	.75	.80	.77	.75	.74
9.0	.81	.76	.73	.80	.76	.73	.79	.76	.73	.79	.75	.73	.78	.75	.72	.71
10.0	.78	.74	.71	.78	.73	.71	.77	.73	.70	.76	.73	.70	.76	.72	.70	.69



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:5.850m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:48.00V I:0.2889A P:13.87W PF:1.000 Freq:0Hz Lamp Flux:931.938x1 lm		
NAME: ML26-PS55-14W-930-36	TYPE:Low Voltage Track System Module	
SPEC.:3000K	DIM.: \varnothing 55mm*H180mm	
MFR.: NEKO LIGHTING AG		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.144	.082	.026	.137	.078	.025	.125	.071	.023	.113	.065	.021	.103	.059	.019		
2.0	.134	.073	.023	.129	.071	.022	.118	.066	.020	.109	.061	.019	.100	.057	.018		
3.0	.126	.067	.020	.121	.065	.020	.113	.061	.019	.105	.057	.018	.097	.054	.017		
4.0	.118	.062	.018	.115	.060	.018	.107	.057	.017	.100	.054	.016	.094	.051	.016		
5.0	.112	.057	.017	.109	.056	.016	.102	.053	.016	.097	.051	.015	.091	.049	.015		
6.0	.106	.053	.015	.104	.052	.015	.098	.050	.015	.093	.048	.014	.088	.047	.014		
7.0	.101	.050	.014	.099	.049	.014	.094	.048	.014	.090	.046	.013	.086	.044	.013		
8.0	.097	.047	.013	.095	.047	.013	.091	.045	.013	.087	.044	.013	.083	.043	.012		
9.0	.093	.045	.013	.091	.044	.012	.087	.043	.012	.084	.042	.012	.080	.041	.012		
10.0	.089	.043	.012	.087	.042	.012	.084	.041	.012	.081	.040	.011	.078	.039	.011		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.169	.158	.148	.144	.135	.127	.099	.093	.088	.057	.054	.051	.018	.017	.017	
2.0	.151	.133	.117	.130	.114	.101	.089	.079	.071	.051	.046	.041	.016	.015	.013	
3.0	.137	.113	.095	.117	.098	.082	.080	.068	.058	.046	.040	.034	.015	.013	.011	
4.0	.125	.098	.078	.107	.085	.068	.074	.059	.048	.043	.035	.028	.014	.011	.009	
5.0	.114	.086	.065	.098	.074	.056	.068	.052	.040	.039	.030	.024	.013	.010	.008	
6.0	.106	.076	.055	.091	.066	.048	.063	.046	.034	.036	.027	.020	.012	.009	.007	
7.0	.099	.068	.047	.085	.059	.041	.059	.041	.029	.034	.024	.017	.011	.008	.006	
8.0	.092	.061	.040	.079	.053	.035	.055	.037	.025	.032	.022	.015	.010	.007	.005	
9.0	.087	.056	.035	.075	.048	.030	.052	.034	.022	.030	.020	.013	.010	.007	.004	
10.0	.082	.051	.031	.071	.044	.027	.049	.031	.019	.029	.018	.011	.009	.006	.004	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:5.850m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.2889A P:13.87W PF:1.000 Freq:0Hz Lamp Flux:931.938x1 lm										
NAME: ML26-PS55-14W-930-36					TYPE:Low Voltage Track System Module					
SPEC.:3000K					DIM.: \varnothing 55mm*H180mm					
MFR.: NEKO LIGHTING AG										
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	12.5	13.2	12.7	13.4	13.5	13.5	14.2	13.7	14.3	14.5
3H	12.4	13.0	12.6	13.2	13.4	13.3	14.0	13.6	14.2	14.3
4H	12.3	12.9	12.6	13.1	13.3	13.2	13.9	13.5	14.1	14.3
6H	12.2	12.8	12.5	13.0	13.3	13.1	13.7	13.4	14.0	14.2
8H	12.2	12.7	12.5	13.0	13.2	13.1	13.7	13.4	13.9	14.2
12H	12.1	12.7	12.4	12.9	13.2	13.1	13.6	13.4	13.9	14.1
4H 2H	12.3	12.9	12.6	13.1	13.4	13.2	13.9	13.5	14.1	14.3
3H	12.1	12.7	12.4	12.9	13.2	13.1	13.6	13.4	13.9	14.1
4H	12.0	12.5	12.4	12.8	13.1	13.0	13.5	13.3	13.8	14.1
6H	11.9	12.4	12.3	12.7	13.1	12.9	13.3	13.2	13.6	14.0
8H	11.9	12.3	12.3	12.6	13.0	12.8	13.2	13.2	13.6	13.9
12H	11.8	12.2	12.2	12.6	13.0	12.8	13.1	13.2	13.5	13.9
8H 4H	11.9	12.3	12.3	12.6	13.0	12.8	13.2	13.2	13.6	13.9
6H	11.8	12.1	12.2	12.5	12.9	12.7	13.0	13.1	13.4	13.8
8H	11.7	12.0	12.2	12.4	12.9	12.6	12.9	13.1	13.4	13.8
12H	11.7	11.9	12.1	12.4	12.8	12.6	12.8	13.0	13.3	13.7
12H 4H	11.8	12.2	12.2	12.6	13.0	12.8	13.1	13.2	13.5	13.9
6H	11.7	12.0	12.2	12.4	12.9	12.6	12.9	13.1	13.4	13.8
8H	11.7	11.9	12.1	12.4	12.8	12.6	12.8	13.0	13.3	13.7
Variations with the observer position at spacings:										
S = 1.0H	+ 2.7 / -15.2					+ 3.1 / -14.4				
1.5H	+ 5.0 / - 9.5					+ 5.2 / -10.4				
2.0H	+ 5.6 / -15.3					+ 7.1 / -15.9				

CIE Pub.117, 931.9 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = -0.2$)

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:5.850m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.2889A P:13.87W PF:1.000 Freq:0Hz Lamp Flux:931.938x1 lm		
NAME: ML26-PS55-14W-930-36	TYPE:Low Voltage Track System Module	
SPEC.:3000K	DIM.: \varnothing 55mm*H180mm	
MFR.: NEKO LIGHTING AG		


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	90	85	81	90	84	81	89	84	81	78
0.80	97	92	89	97	92	89	96	91	88	85
1.00	101	96	93	101	96	93	99	96	92	89
1.25	105	100	97	104	100	97	102	99	96	92
1.50	107	103	100	106	102	100	104	101	99	94
2.00	110	106	103	108	105	102	106	103	101	96
2.50	111	108	105	110	106	104	107	104	102	96
3.00	113	109	107	111	108	106	107	105	104	97
4.00	114	112	110	112	110	109	109	107	106	99
5.00	116	114	112	114	112	110	110	108	107	100
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Jason
 Test Date:2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:58%
 Test Distance:5.850m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.2889A P:13.87W PF:1.000 Freq:0Hz Lamp Flux:931.938x1 lm		
NAME: ML26-PS55-14W-930-36	TYPE:Low Voltage Track System Module	
SPEC.:3000K	DIM.: ϕ 55mm*H180mm	
MFR.: NEKO LIGHTING AG		




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:5.850m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.2889A P:13.87W PF:1.000 Freq:0Hz Lamp Flux:931.938x1 lm		
NAME: ML26-PS55-14W-930-36	TYPE:Low Voltage Track System Module	
SPEC.:3000K	DIM.: ϕ 55mm*H180mm	
MFR.: NEKO LIGHTING AG		




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:5.850m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:48.00V I:0.2889A P:13.87W PF:1.000 Freq:0Hz Lamp Flux:931.938x1 lm		
NAME: ML26-PS55-14W-930-36	TYPE:Low Voltage Track System Module	
SPEC.:3000K	DIM.: ϕ 55mm*H180mm	
MFR.: NEKO LIGHTING AG		



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:5.850m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:48.00V I:0.2889A P:13.87W PF:1.000 Freq:0Hz Lamp Flux:931.938x1 lm		
NAME: ML26-PS55-14W-930-36	TYPE:Low Voltage Track System Module	
SPEC.:3000K	DIM.: ϕ 55mm*H180mm	
MFR.: NEKO LIGHTING AG		


AvgL	cd/m2
L_0~180 (65) av	164
L_0~180 (75) av	72
L_0~180 (85) av	161
L_90~270 (65) av	136
L_90~270 (75) av	72
L_90~270 (85) av	166
L_45 (65) av	146
L_45 (75) av	70
L_45 (85) av	163

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:5.850m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Jason
Test Date: 2020-05-08

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity: 58%
Test Distance: 5.850m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:5.850m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:58%
Test Distance:5.850m [K=1.0000]
Remarks:

```