

Model No.	MINUX 38	MINUX 44	MINUX 57
Product Photo			
Dimension (mm)			
Cutout (mm)			
Wattage	6W	9W	13W
CCT	2700K/ 3000K/ 4000K	2700K/ 3000K/ 4000K	2700K/ 3000K/ 4000K
CRI	>90	>90	>90
Beam Angle	18°/ 38°/ 50°	20°/ 40°/ 50°	18°/ 36°/ 50°
Lumen Output	450lm @CRI90 3000K	850lm @CRI90 3000K	1000lm @CRI90 3000K
IP	IP54		IP54
Dimming	On/ Off, Phase Dim, 0/1 -10V Dim, DALI Dim		On/ Off, Phase Dim, 0/1 -10V Dim, DALI Dim
Accessory	 honeycomb		 honeycomb
Trimless Version			
Reflector Color	 Dark Light Matt White Black Gold		 Dark Light Matt White Black Gold
Trim Color	Standard: White Available: Black/ Customized 		Standard: White Available: Black/ Customized



White Reflector



Gold Reflector

6 W	8 W	12 V	500 mA	90	2700K	18°	500lm	420lm	MIF3-9271806N-WW
						38°	500lm	420lm	MIF3-9273806N-WW
						50°	500lm	420lm	MIF3-9275006N-WW
					3000K	18°	550lm	450lm	MIF3-9301806N-WW
						38°	550lm	450lm	MIF3-9303806N-WW
						50°	550lm	450lm	MIF3-9305006N-WW
					4000K	18°	600lm	500lm	MIF3-9401806N-WW
						38°	600lm	500lm	MIF3-9403806N-WW
						50°	600lm	500lm	MIF3-9405006N-WW

Code Remark: N=N(No Driver) F=F(ON-OFF) P=P(Phase Dim) A=A(1-10V Dim) D=D(DALI Dim)

Trimless Version available



Trimless code for MIF3-9405006N-WM → MIT3-9405006N-WM



Preinstall Trimless code for MIF3-9405006N-WM → MIE3-9405006N-WM



6W	CRI90	2700K 3000K 4000K	18° 38° 50°	CITIZEN 50,000h@L80B10	UGR < 19	IP54	5 GUARANTEED	CB	CE	ETL Intertek
----	-------	-------------------------	-------------------	---------------------------	-------------	------	-----------------	----	----	-----------------



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
6 W	8 W	12 V	500 mA	90	2700K	18°	500lm	420lm	MIF3-9271806N-WM	
						38°	500lm	420lm	MIF3-9273806N-WM	
						50°	500lm	420lm	MIF3-9275006N-WM	
						3000K	18°	550lm	450lm	MIF3-9301806N-WM
							38°	550lm	450lm	MIF3-9303806N-WM
							50°	550lm	450lm	MIF3-9305006N-WM
						4000K	18°	600lm	500lm	MIF3-9401806N-WM
							38°	600lm	500lm	MIF3-9403806N-WM
							50°	600lm	500lm	MIF3-9405006N-WM
6 W	8 W	12 V	500 mA	90	2700K	18°	500lm	420lm	MIF3-9271806N-WB	
						38°	500lm	420lm	MIF3-9273806N-WB	
						50°	500lm	420lm	MIF3-9275006N-WB	
						3000K	18°	550lm	450lm	MIF3-9301806N-WB
							38°	550lm	450lm	MIF3-9303806N-WB
							50°	550lm	450lm	MIF3-9305006N-WB
						4000K	18°	600lm	500lm	MIF3-9401806N-WB
							38°	600lm	500lm	MIF3-9403806N-WB
							50°	600lm	500lm	MIF3-9405006N-WB
6 W	8 W	12 V	500 mA	90	2700K	18°	500lm	420lm	MIF3-9271806N-WC	
						38°	500lm	420lm	MIF3-9273806N-WC	
						50°	500lm	420lm	MIF3-9275006N-WC	
						3000K	18°	550lm	450lm	MIF3-9301806N-WC
							38°	550lm	450lm	MIF3-9303806N-WC
							50°	550lm	450lm	MIF3-9305006N-WC
						4000K	18°	600lm	500lm	MIF3-9401806N-WC
							38°	600lm	500lm	MIF3-9403806N-WC
							50°	600lm	500lm	MIF3-9405006N-WC

Code Remark: N=N(No Driver) F=F(ON-OFF) P=P(Phase Dim) A=A(1-10V Dim) D=D(DALI Dim)



Matt Reflector



Black Reflector



Dark Light Reflector

Optional accessory



Code for MIF3-9305006N-WM with Honeycomb
MIF3-9305006N-WM-H



White Reflector



Gold Reflector


9 W	11 W	36 V	250 mA	90	2700K	20°	950lm	800lm	MIF4-9272009N-WW
						40°	950lm	800lm	MIF4-9274009N-WW
						50°	950lm	800lm	MIF4-9275009N-WW
					3000K	20°	1000lm	850lm	MIF4-9302009N-WW
						40°	1000lm	850lm	MIF4-9304009N-WW
						50°	1000lm	850lm	MIF4-9305009N-WW
					4000K	20°	1050lm	900lm	MIF4-9402009N-WW
						40°	1050lm	900lm	MIF4-9404009N-WW
						50°	1050lm	900lm	MIF4-9405009N-WW

Code Remark: N=N(No Driver) F=F(ON-OFF) P=P(Phase Dim) A=A(1-10V Dim) D=D(DALI Dim)

Trimless Version available




Trimless code for MIF4-9405009N-WM → MIT4-9405009N-WM



Preinstall Trimless code for MIF4-9405009N-WM → MIE4-9405009N-WM



9W	CRI90	2700K 3000K 4000K	20° 40° 50°	CITIZEN 50,000h@L80B10	UGR < 19	IP54	5 GUARANTEED	CB	CE	ETL Intertek
----	-------	-------------------------	-------------------	---------------------------	-------------	------	-----------------	----	----	-----------------



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
9 W	11 W	36 V	250 mA	90	2700K	20°	950lm	800lm	MIF4-9272009N-WM
						40°	950lm	800lm	MIF4-9274009N-WM
						50°	950lm	800lm	MIF4-9275009N-WM
					3000K	20°	1000lm	850lm	MIF4-9302009N-WM
						40°	1000lm	850lm	MIF4-9304009N-WM
						50°	1000lm	850lm	MIF4-9305009N-WM
					4000K	20°	1050lm	900lm	MIF4-9402009N-WM
						40°	1050lm	900lm	MIF4-9404009N-WM
						50°	1050lm	900lm	MIF4-9405009N-WM

Code Remark: N=N(No Driver) F=F(ON-OFF) P=P(Phase Dim) A=A(1-10V Dim) D=D(DALI Dim)



Matt Reflector



Black Reflector



Dark Light Reflector

Optional accessory




Code for MIF4-9305009N-WM with Honeycomb
MIF4-9305009N-WM-H

Honeycomb



13W	CRI90	2700K 3000K 4000K	18° 36° 50°	CITIZEN 50,000h@L80B10	UGR < 19	IP54	5 GUARANTEED	CB	CE	ETL Intertek
-----	-------	-------------------------	-------------------	----------------------------------	-------------	------	-----------------	----	----	-----------------



13 W	15 W	36 V	350 mA	90	2700K	20° 40° 50°	1200lm 1200lm 1200lm	950lm 950lm 950lm	MIF5-9271813N-WW MIF5-9273613N-WW MIF5-9275013N-WW
					3000K	20° 40° 50°	1300lm 1300lm 1300lm	1000lm 1000lm 1000lm	MIF5-9301813N-WW MIF5-9303613N-WW MIF5-9305013N-WW
					4000K	20° 40° 50°	1400lm 1400lm 1400lm	1050lm 1050lm 1050lm	MIF5-9401813N-WW MIF5-9403613N-WW MIF5-9405013N-WW

Code Remark: N=N(No Driver) F=F(ON-OFF) P=P(Phase Dim) A=A(1-10V Dim) D=D(DALI Dim)


Trimless Version available



Trimless code for MIF5-9405013N-WM → MIT5-9405013N-WM



Preinstall Trimless code for MIF5-9405013N-WM → MIE5-9405013N-WM



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
13 W	15 W	36 V	350 mA	90	2700K	18°	1200lm	950lm	MIF5-9271813N-WM
						36°	1200lm	950lm	MIF5-9273613N-WM
						50°	1200lm	950lm	MIF5-9275013N-WM
					3000K	18°	1300lm	1000lm	MIF5-9301813N-WM
						36°	1300lm	1000lm	MIF5-9303613N-WM
						50°	1300lm	1000lm	MIF5-9305013N-WM
					4000K	18°	1400lm	1050lm	MIF5-9401813N-WM
						36°	1400lm	1050lm	MIF5-9403613N-WM
						50°	1400lm	1050lm	MIF5-9405013N-WM

Code Remark: N=N(No Driver) F=F(ON-OFF) P=P(Phase Dim) A=A(1-10V Dim) D=D(DALI Dim)

Optional accessory



Code for MIF5-9305013N-WM with Honeycomb
MIF5-9305013N-WM-H