

NEKO / GAME

Project: Skyline Hill, Germany





**NEKO / GAME350**  
Ceiling Light System

12W CRI80 2700K Tunable White  
18W CRI90 3000K Available  
4000K

90° OSRAM 50,000h@L80B10 UGR < 19 IP40 5 YEARS GUARANTEED CB CE



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code						
12 W	14 W	36 V	350 mA	80	2700K	90°	1800lm	1300lm	GASM-8279012X-BN						
						3000K 90°	1900lm	1400lm	GASM-8309012X-BN						
						4000K 90°	2000lm	1500lm	GASM-8409012X-BN						
						18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GASM-8279018X-BN
												3000K 90°	2600lm	2000lm	GASM-8309018X-BN
												4000K 90°	2800lm	2200lm	GASM-8409018X-BN
12 W	14 W	36 V	350 mA	80	2700K	90°	1800lm	1300lm	GASM-8279012X-WN						
						3000K 90°	1900lm	1400lm	GASM-8309012X-WN						
						4000K 90°	2000lm	1500lm	GASM-8409012X-WN						
						18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GASM-8279018X-WN
												3000K 90°	2600lm	2000lm	GASM-8309018X-WN
												4000K 90°	2800lm	2200lm	GASM-8409018X-WN

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)

Optional accessory



Magnetic Uplight Module 350

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
8 W	10 W	33 V	250 mA	80	2700K	110	900lm	800lm	UM35-827A108X-NN
						3000K 110	950lm	850lm	UM35-830A108X-NN
						4000K 110	1050lm	950lm	UM35-840A108X-NN

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)

Code for GPR-8309012X-WN with Uplight Module  
GAPR-8309012X-WN-U



Standard pendant length: 1200mm Black

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
12 W	14 W	36 V	350 mA	80	2700K	90°	1800lm	1300lm	GAPW-8279012X-BN
					3000K	90°	1900lm	1400lm	GAPW-8309012X-BN
					4000K	90°	2000lm	1500lm	GAPW-8409012X-BN
18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GAPW-8279018X-BN
					3000K	90°	2600lm	2000lm	GAPW-8309018X-BN
					4000K	90°	2800lm	2200lm	GAPW-8409018X-BN



Standard pendant length: 1200mm White

12 W	14 W	36 V	350 mA	80	2700K	90°	1800lm	1300lm	GAPW-8279012X-WN
					3000K	90°	1900lm	1400lm	GAPW-8309012X-WN
					4000K	90°	2000lm	1500lm	GAPW-8409012X-WN
18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GAPW-8279018X-WN
					3000K	90°	2600lm	2000lm	GAPW-8309018X-WN
					4000K	90°	2800lm	2200lm	GAPW-8409018X-WN



Standard pendant length: 1000mm Black

12 W	14 W	36 V	350 mA	80	2700K	90°	1800lm	1300lm	GAPR-8279012X-BN
					3000K	90°	1900lm	1400lm	GAPR-8309012X-BN
					4000K	90°	2000lm	1500lm	GAPR-8409012X-BN
18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GAPR-8279018X-BN
					3000K	90°	2600lm	2000lm	GAPR-8309018X-BN
					4000K	90°	2800lm	2200lm	GAPR-8409018X-BN

Remark: Pendant Rod Cuttable



Standard pendant length: 1000mm White

12 W	14 W	36 V	350 mA	80	2700K	90°	1800lm	1300lm	GAPR-8279012X-WN
					3000K	90°	1900lm	1400lm	GAPR-8309012X-WN
					4000K	90°	2000lm	1500lm	GAPR-8409012X-WN
18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GAPR-8279018X-WN
					3000K	90°	2600lm	2000lm	GAPR-8309018X-WN
					4000K	90°	2800lm	2200lm	GAPR-8409018X-WN

Remark: Pendant Rod Cuttable

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)

**NEKO / GAME450**  
Ceiling Light System

18W CRI80 2700K Tunable White  
25W CRI90 3000K Available  
4000K



**OSRAM**  
50,000h@L80B10

**UGR**  
< 19

**IP40**



**CB CE**



Black

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GBSM-8279018X-BN
					3000K	90°	2600lm	2000lm	GBSM-8309018X-BN
					4000K	90°	2800lm	2200lm	GBSM-8409018X-BN
25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GBSM-8279025X-BN
					3000K	90°	3700lm	2800lm	GBSM-8309025X-BN
					4000K	90°	4000lm	3000lm	GBSM-8409025X-BN



White

18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GBSM-8279018X-WN
					3000K	90°	2600lm	2000lm	GBSM-8309018X-WN
					4000K	90°	2800lm	2200lm	GBSM-8409018X-WN
25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GBSM-8279025X-WN
					3000K	90°	3700lm	2800lm	GBSM-8309025X-WN
					4000K	90°	4000lm	3000lm	GBSM-8409025X-WN

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)

Optional accessory



Magnetic Uplight Module 450



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
11 W	13 W	33 V	350 mA	80	2700K	110°	1100lm	1000lm	UM45-827A111X-NN
					3000K	110°	1200lm	1100lm	UM45-830A111X-NN
					4000K	110°	1300lm	1200lm	UM45-840A111X-NN

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)

Code for GAPR-8309012X-WN with Uplight Module

GAPR-8309012X-WN-U



Standard pendant length: 1200mm Black

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GBPW-8279018X-BN
					3000K	90°	2600lm	2000lm	GBPW-8309018X-BN
					4000K	90°	2800lm	2200lm	GBPW-8409018X-BN
25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GBPW-8279025X-BN
					3000K	90°	3700lm	2800lm	GBPW-8309025X-BN
					4000K	90°	4000lm	3000lm	GBPW-8409025X-BN



Standard pendant length: 1200mm White

18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GBPW-8279018X-WN
					3000K	90°	2600lm	2000lm	GBPW-8309018X-WN
					4000K	90°	2800lm	2200lm	GBPW-8409018X-WN
25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GBPW-8279025X-WN
					3000K	90°	3700lm	2800lm	GBPW-8309025X-WN
					4000K	90°	4000lm	3000lm	GBPW-8409025X-WN



Standard pendant length: 1000mm Black

18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GBPR-8279018X-BN
					3000K	90°	2600lm	2000lm	GBPR-8309018X-BN
					4000K	90°	2800lm	2200lm	GBPR-8409018X-BN
25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GBPR-8279025X-BN
					3000K	90°	3700lm	2800lm	GBPR-8309025X-BN
					4000K	90°	4000lm	3000lm	GBPR-8409025X-BN

Remark: Pendant Rod Cuttable



Standard pendant length: 1000mm White

18 W	20 W	36 V	500 mA	80	2700K	90°	2400lm	1900lm	GBPR-8279018X-WN
					3000K	90°	2600lm	2000lm	GBPR-8309018X-WN
					4000K	90°	2800lm	2200lm	GBPR-8409018X-WN
25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GBPR-8279025X-WN
					3000K	90°	3700lm	2800lm	GBPR-8309025X-WN
					4000K	90°	4000lm	3000lm	GBPR-8409025X-WN

Remark: Pendant Rod Cuttable

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)



Code for GBPR-8279018X-WW with Uplight Module  
GBPR-8279018X-WW-U



# NEKO / GAME600

## Ceiling Light System

25W  
38W  
50W

CRI80  
CRI90

2700K  
3000K  
4000K

Tunable White Available

90°


OSRAM  
50,000h@L80B10

UGR < 19

IP40

5 YEARS GUARANTEE

CB CE



Black

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GCSM-8279025X-BN
					3000K	90°	3700lm	2800lm	GCSM-8309025X-BN
					4000K	90°	4000lm	3000lm	GCSM-8409025X-BN
38 W	42 W	36 V	1050 mA	80	2700K	90°	5800lm	4400lm	GCSM-8279038X-BN
					3000K	90°	6200lm	4700lm	GCSM-8309038X-BN
					4000K	90°	6600lm	4900lm	GCSM-8409038X-BN
50 W	54 W	36 V	1400 mA	80	2700K	90°	7200lm	5800lm	GCSM-8279050X-BN
					3000K	90°	8100lm	6100lm	GCSM-8309050X-BN
					4000K	90°	8600lm	6400lm	GCSM-8409050X-BN



White

25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GCSM-8279025X-WN
					3000K	90°	3700lm	2800lm	GCSM-8309025X-WN
					4000K	90°	4000lm	3000lm	GCSM-8409025X-WN
38 W	42 W	36 V	1050 mA	80	2700K	90°	5800lm	4400lm	GCSM-8279038X-WN
					3000K	90°	6200lm	4700lm	GCSM-8309038X-WN
					4000K	90°	6600lm	4900lm	GCSM-8409038X-WN
50 W	54 W	36 V	1400 mA	80	2700K	90°	7200lm	5800lm	GCSM-8279050X-WN
					3000K	90°	8100lm	6100lm	GCSM-8309050X-WN
					4000K	90°	8600lm	6400lm	GCSM-8409050X-WN

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)

### Optional accessory



Magnetic Uplight Module 600

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
18 W	20 W	36 V	500 mA	80	2700K	110	1800lm	1600lm	UM60-827A118X-NN
					3000K	110	1900lm	1700lm	UM60-830A118X-NN
					4000K	110	2000lm	1800lm	UM60-840A118X-NN

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)

Code for GAPR-8309012X-WN with Uplight Module  
GAPR-8309012X-WN-U



Standard pendant length: 1200mm Black

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GCPW-8279025X-BN
					3000K	90°	3700lm	2800lm	GCPW-8309025X-BN
					4000K	90°	4000lm	3000lm	GCPW-8409025X-BN
38 W	42 W	36 V	1050 mA	80	2700K	90°	5800lm	4400lm	GCPW-8279038X-BN
					3000K	90°	6200lm	4700lm	GCPW-8309038X-BN
					4000K	90°	6600lm	4900lm	GCPW-8409038X-BN
50 W	54 W	36 V	1400 mA	80	2700K	90°	7200lm	5800lm	GCPW-8279050X-BN
					3000K	90°	8100lm	6100lm	GCPW-8309050X-BN
					4000K	90°	8600lm	6400lm	GCPW-8409050X-BN



Standard pendant length: 1200mm White

25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GCPW-8279025X-WN
					3000K	90°	3700lm	2800lm	GCPW-8309025X-WN
					4000K	90°	4000lm	3000lm	GCPW-8409025X-WN
38 W	42 W	36 V	1050 mA	80	2700K	90°	5800lm	4400lm	GCPW-8279038X-WN
					3000K	90°	6200lm	4700lm	GCPW-8309038X-WN
					4000K	90°	6600lm	4900lm	GCPW-8409038X-WN
50 W	54 W	36 V	1400 mA	80	2700K	90°	7200lm	5800lm	GCPW-8279050X-WN
					3000K	90°	8100lm	6100lm	GCPW-8309050X-WN
					4000K	90°	8600lm	6400lm	GCPW-8409050X-WN



Standard pendant length: 1000mm Black

25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GCPR-8279025X-BN
					3000K	90°	3700lm	2800lm	GCPR-8309025X-BN
					4000K	90°	4000lm	3000lm	GCPR-8409025X-BN
38 W	42 W	36 V	1050 mA	80	2700K	90°	5800lm	4400lm	GCPR-8279038X-BN
					3000K	90°	6200lm	4700lm	GCPR-8309038X-BN
					4000K	90°	6600lm	4900lm	GCPR-8409038X-BN
50 W	54 W	36 V	1400 mA	80	2700K	90°	7200lm	5800lm	GCPR-8279050X-BN
					3000K	90°	8100lm	6100lm	GCPR-8309050X-BN
					4000K	90°	8600lm	6400lm	GCPR-8409050X-BN

Remark: Pendant Rod Cuttable



Standard pendant length: 1000mm White

25 W	28 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GCPR-8279025X-WN
					3000K	90°	3700lm	2800lm	GCPR-8309025X-WN
					4000K	90°	4000lm	3000lm	GCPR-8409025X-WN
38 W	42 W	36 V	1050 mA	80	2700K	90°	5800lm	4400lm	GCPR-8279038X-WN
					3000K	90°	6200lm	4700lm	GCPR-8309038X-WN
					4000K	90°	6600lm	4900lm	GCPR-8409038X-WN
50 W	54 W	36 V	1400 mA	80	2700K	90°	7200lm	5800lm	GCPR-8279050X-WN
					3000K	90°	8100lm	6100lm	GCPR-8309050X-WN
					4000K	90°	8600lm	6400lm	GCPR-8409050X-WN


Remark: Pendant Rod Cuttable

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)



**NEKO / GAME900**  
Ceiling Light System

65W | CRI80 | 2700K | 3000K | 4000K | 90° | OSRAM | UGR < 19 | IP40 | 5 YEARS GUARANTEE | CB | CE



Black

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDSM-8279065X-BN
					3000K	90°	10500lm	8000lm	GDSM-8309065X-BN
					4000K	90°	11000lm	8400lm	GDSM-8409065X-BN



White

65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDSM-8279065X-WN
					3000K	90°	10500lm	8000lm	GDSM-8309065X-WN
					4000K	90°	11000lm	8400lm	GDSM-8409065X-WN

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)

Optional accessory



Magnetic Uplight Module 900

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
25 W	28 W	36 V	700 mA	80	2700K	110	2500lm	2200lm	UM90-827A125X-NN
					3000K	110	2700lm	2400lm	UM90-830A125X-NN
					4000K	110	2900lm	2600lm	UM90-840A125X-NN

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)

Code for GAPR-8309012X-WN with Uplight Module  
GAPR-8309012X-WN-U





Standard pendant length: 1200mm Black

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDPW-8279065X-BN
					3000K	90°	10500lm	8000lm	GDPW-8309065X-BN
					4000K	90°	11000lm	8400lm	GDPW-8409065X-BN



Standard pendant length: 1200mm White

65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDPW-8279065X-WN
					3000K	90°	10500lm	8000lm	GDPW-8309065X-WN
					4000K	90°	11000lm	8400lm	GDPW-8409065X-WN



Standard pendant length: 1000mm Black

65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDPR-8279065X-BN
					3000K	90°	10500lm	8000lm	GDPR-8309065X-BN
					4000K	90°	11000lm	8400lm	GDPR-8409065X-BN

Remark: Pendant Rod Cuttable



Standard pendant length: 1000mm White

65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDPR-8279065X-WN
					3000K	90°	10500lm	8000lm	GDPR-8309065X-WN
					4000K	90°	11000lm	8400lm	GDPR-8409065X-WN

Remark: Pendant Rod Cuttable

Code Remark: X=F(ON-OFF) X=P(Phase Dim) X=A(1-10V Dim) X=D(DALI Dim)

**NEKO / GAME**

Project: Skyline Hill, Germany



